

Overview Options



Large Industrial Gearbox Options

Options	Option Code	Description	Output Design	Output Options	Input Design	Add. Options	Size							⇒				
							SK 5.07	SK 6.07	SK 7.07	SK 8.07	SK 9.07	SK 10.07	SK 11.07	SK 12.07	SK 13.07	SK 14.07	SK 15.07	
	A	Keyed hollow output shaft	X				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	64
	AS	Keyed hollow for shrink disc	X				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	66
	B	Fixing kit for hollow output shaft		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	65
	CC	Internal water cooler			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	81
	CS1	External oil / water cooler				X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	84
	CS2	External oil / air cooler				X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	84
	D	Torque support		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	74
	DRY	Spread Bearing Design "True Drywell" with standard bearing		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	64
	EA	Hollow output shaft, with spline, DIN 5480	X				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	64
	ED	Elastic torque support		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	74
	EV	Splined solid output shaft, DIN 5480	X				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	64
	EW	Splined solid input shaft, DIN 5480		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	64
	F	Low output flange (B14 with threaded holes)		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	70
	FAN	Fan or Electric Fan			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	84
	FK	High output flange (B5 with through holes)		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	70
	F1	Input flange (SK .207 / SK .307)		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	77
	H/H66	Cover (contact protection) / IP66 Cover		X	X		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	67
	IEC	Adapter for fitting B5 IEC standard motors		X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	77
	L	Double solid output shaft	X				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	64
	LC	Pressure Forced lubrication (Bearings)			X	-	-	1)	1)	1)	1)	1)	✓	✓	✓	✓	✓	82
	LCX	Pressure Forced lubrication with Drywell (Bearings & Gears)			X	-	-	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	82
	MC	Motor scoop			X	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	77
	MO	Monitoring devices & sensors			X	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	78
	MF	Motor base frame (options: see MF..)		X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	74
	MFB	Base frame with brake		X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75

¹⁾ on request



Option Code	Description	Output Design	Output Options	Input Design	Add. Options	Size										↓	
						SK 5.07	SK 6.07	SK 7.07	SK 8.07	SK 9.07	SK 10.07	SK 11.07	SK 12.07	SK 13.07	SK 14.07	SK 15.07	
MS	Motor Swing Base (options: see MS ..)			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	74
MSB	Swing base with brake			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MFK	Base frame with elastic coupling			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MFT	Base frame with fluid coupling			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MSK	Swing base with elastic coupling			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MSKB	Swing base with elastic coupling and brake			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MST	Swing base with fluid coupling			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MFTB	Base frame with fluid coupling and brake			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MSTB	Swing base with fluid coupling and brake			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
MT	Motor bracket			X	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	1)	78
NEMA	Adapter for fitting B5 NEMA C-flange standard motors		X		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	77
OT	Oil tank		X		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	83
OH	Oil heater		X		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	83
R *	Backstop		X		✓*	✓*	✓*	✓*	✓*	✓*	✓*	✓*	✓	✓	✓	✓	69
V	Solid output shaft	X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	64
VL2	Spread Bearing Design	X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	71
VL3	Spread Bearing Design with Oil Safe Dry Cavity	X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	71
VL4	Spread Bearing Design with Drywell	X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	72
VL5	Extruder Flange	X			✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-	72
VL6	Spread Bearing Design with "True Drywell" without Flange	X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	72
WX	Auxiliary drive		X		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	78
WG	Primery gear		X		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	---
W1 W2 * W3 *	W1/2/3 - number of Solid Shaft Input W3 - for type 407 and 507		X		✓*	✓*	✓*	✓*	✓*	✓*	✓*	✓	✓	✓	✓	✓	---
---	Brakes			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	76
---	Couplings		X X		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	76
---	Paint Coatings			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	79
---	Endurance Package			X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	86